MANITOU MANISCOPIC MRT MRT 2150 M SERIES PERKINS 1104C-44TA



ENGINE Perkins 1104C-44TA Capacity: 7,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours/3 months

DIFFERENTIAL FRONT Capacity: 11 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Chock overy 250 hours, change over	ony 1000 hours/12 months	·	

Check every 250 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR Capacity: 11 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Charles and 250 have about			

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT Capacity: 1,6 liter (each hub)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Check every 250 hours, change ev	rery 1000 hours/ 12 months		

HUB REDUCTIONS REAR Capacity: 1,6 liter (each hub)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Check every 250 hours, change ev	ery 1000 hours/ 12 months		

MANITOU MANISCOPIC MRT MRT 2150 M SERIES PERKINS 1104C-44TA



TRANSFERBOX 2/2 Capacity: 2,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 250 hours, change every 1000 hours/12 months

HYDRAULIC SYSTEM Capacity: 200 liter (Tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 50 hours, change every 100	0 hours/ 12 months	

AXLE OSCILLATION REAR

USE

Normal

PRODUCT RECOMMENDATION 2

Labora Grease

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

Change every 250 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 250 hours	1	1

ROTATION RING GEAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Change every 250 hours	

MANITOU MANISCOPIC MRT MRT 2150 M SERIES PERKINS 1104C-44TA



COOLING SYSTEM Capacity: 25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

ROTATION REDUCER Capacity: 2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Check every 250 hours, change ev	rery 1000 hours/ 12 months	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.