MANITOU MANITRANSIT RANGE TMD/TME/TMP/TMT/TMV TMT 315 KUBOTA D1105-E (1999-2005)



| ENGINE Kubota D1105-E Capacity: 5,1 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |
| Check every 10 hours change even | v 100 hours | |

Check every 10 hours, change every 100 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |

Check every 10 hours, change every 100 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |

Change every 50 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |
| Change every 50 hours | · | |

| Normal Moderate PRODUCT RECOMMENDATION 1 | |
|---|--|
| | |
| PRODUCT RECOMMENDATION 1 | |
| | |
| Perlus H 46 | |

Check every 10 hours, change every 800 hours/ 12 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| | I | I |

MANITOU MANITRANSIT RANGE TMD/TME/TMP/TMT/TMV TMT 315 KUBOTA D1105-E (1999-2005)



| COOLING SYSTEM Capacity: 3,1 liter | | |
|------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |
| Check every 10 hours, change eve | ry 400 hours/ 12 months | - |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.