

MASSEY FERGUSON 3600 MF 3625 S (2013-2018)



ENGINE Sisu 33DTA
Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT Carraro
Capacity: 3 liter (30 km/h version), Capacity: 3 liter (40 km/h version)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 400 hours, change every 800 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

HUB REDUCTIONS FRONT Carraro
Capacity: 0,4 liter (30 km/h version), Capacity: 0,4 liter (40 km/h version)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 400 hours, change every 800 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

MASSEY FERGUSON 3600 MF 3625 S (2013-2018)



TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 36-39 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40*Check every 10 hours, change every 1200 hours*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

LHM +*Check every 10 hours, change every 24 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multi Purpose Grease 3*Change every 50 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Change every 50 hours*

MASSEY FERGUSON 3600 MF 3625 S (2013-2018)



COOLING SYSTEM

Capacity: 11 liter (+ cabin), Capacity: 10 liter (Without cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.