MASSEY FERGUSON 3600 MF 3640 F (2013-2018)



ENGINE Sisu 33CTA Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40

Check every 10 hours, change every 400 hours

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Check every 400 hours, change eve	ery 800 hours	·	
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

HUB REDUCTIONS FRONT Carraro Capacity: 0,6 liter (30 km/h version), Capacity: 0,6 liter (40 km/h version)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Chack avery 400 hours, change ave	200 hours	

Check every 400 hours, change every 800 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 50 hours	·	

MASSEY FERGUSON 3600 MF 3640 F (2013-2018)



TRANSMISSION/HYDRAULIC SYSTEM Capacity: 36-39 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		
Check every 10 hours, change every 1200 hours		

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
LHM +		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multi Purpose Grease 3		
Change every 50 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	·	·
USE		CLIMATE

USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Grease EP 1	
Change every 50 hours	

MASSEY FERGUSON 3600 MF 3640 F (2013-2018)



COOLING SYSTEM Capacity: 11 liter (+ cabin), Capacity: 10 liter (Without cabin)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	ry 1200 hours	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.