PRODUCT RECOMMENDATION

# MASSEY FERGUSON 3600 MF 3690 (1991-1995)

**ENGINE** Valmet 612\634DS
Capacity: 21 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrisynth LSP Ultra 10W-40** | **Agrisynth LSP 10W-40** | **Kroontrak CVT 10W-40** |

*Change every 250 hours/ 6 months*

**DIFFERENTIAL FRONT** (4x4)
Capacity: 11 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT** (4x4)
Capacity: 1,8 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours, change every 1000 hours/ 12 months*

**REDUCTION UNITS REAR**
Capacity: 5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 85W-140** | **Unigear LS GL-3/GL-5 85W-140** | |

*Check every 250 hours, change every 1000 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM WITH DRY CLUTCH SYSTEM** 16/16
Capacity: 75 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Kroontrak MTH 10W-30** | | |

*Check every 100 hours, change every 1000 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# MASSEY FERGUSON 3600 MF 3690 (1991-1995)

## TRANSAXLE/HYDRAULIC SYSTEM WITH MULTI-DISC WET CLUTCH SYSTEM 16/16

Capacity: 75 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Kroontrak CVT 10W-40** | **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** |

*Check every 100 hours, change every 1000 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Check every 10 hours*

## COOLING SYSTEM

Capacity: 29,7 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

*Check every 100 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367