MASSEY FERGUSON 5400 5455 TIER II

(2004-2008)



ENGINE Perkins 1104D-44T Capacity: 9,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT Carraro Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

DIFFERENTIAL FRONT Dana Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 400 hours, change eve	ery 800 hours	

HUB REDUCTIONS FRONT Carrard Capacity: 0,9 liter	0	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 400 hours, change ever	y 800 hours	

HUB REDUCTIONS FRONT Dana Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 400 hours, change eve	ery 800 hours	

MASSEY FERGUSON 5400 5455 TIER II

(2004-2008)



TRANSAXLE/HYDRAULIC SYSTEM 12/ Capacity: 62 liter (Mechanical transmission	ISAXLE/HYDRAULIC SYSTEM 12/12 city: 62 liter (Mechanical transmission), Capacity: 74 liter (Powershift)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		
Check every 10 hours, change every 1200 hours		

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multi Purpose Grease 3		
Check every 50 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

COOLING SYSTEM Capacity: 25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Chook ayan, 10 haura ahanga ayar	1200 hours	·

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.