

**ABARTH 500C / 595C / 695C 312****500C 1.4 T-JET (99 KW) (2009-2016)****MOTOR 312A1000**

Yağlayıcı kapasitesi: 2,9 litre (Servis ikmali), Filtre kapasitesi: 0,15 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Emperol 5W-50***Değişim her 15000 km/ 12 ay***KULLANIM**

Zor

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Emperol 5W-50***Kontrol her 3000 km, değişim her 10000 km/ 12 ay***DİFERANSİYELİ ŞANZİMAN DÜZ C 514 R 5/1**

Yağlayıcı kapasitesi: 1,65 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Gear 5015****HİDROLİK FREN SİSTEMİ****KULLANIM**

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Drauliquid-LV Super DOT 4****ÜRÜN ÖNERİSİ 2****Drauliquid-S DOT 4***Kontrol her 30000 km, değişim her 60000 km/ 24 ay*



ABARTH 500C / 595C / 695C 312

500C 1.4 T-JET (99 KW) (2009-2016)

SOĞUTMA SİSTEMİ

Yağlayıcı kapasitesi: 5,2 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Coolant SP 14+**

Kontrol her 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.