

ACURA (USA / CAN) TSX CU2 TSX 2.4 (2011-2014)

**MOTOR K24Z3**

Yağlayıcı kapasitesi: 4 litre, Filtre kapasitesi: 0,2 litre

KULLANIM

Esnek (araç üstü bakım sistemi)

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Presteza MSP 0W-20****DİFERANSİYELİ ŞANZİMAN DÜZ 6/1**

Yağlayıcı kapasitesi: 1,9 litre (Servis ikmali)

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Gear 5015****DİFERANSİYELİ ŞANZİMAN OTOMATİK 5/1**

Yağlayıcı kapasitesi: 2,4 litre (Servis ikmali)

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Matic 4036****HİDROLİK FREN SİSTEMİ****KULLANIM**

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Drauliquid DOT 3**

ACURA (USA / CAN) TSX CU2 TSX 2.4 (2011-2014)

**SOĞUTMA SİSTEMİ**

Yağlayıcı kapasitesi: 6,2-6,3 litre (Servis ikmali)

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Coolant SP 14+**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.