



ALFA ROMEO (EU) 156 932 156 1.9 JTD 16V (93 KW) (2002-2005)

MOTOR 937A4000

Yağlayıcı kapasitesi: 4,5 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Emperol 5W-40**

Kontrol her 500 km, değişim her 20000 km/ 12 ay

DİFERANSİYELİ ŞANZİMAN DÜZ 6/1

Yağlayıcı kapasitesi: 2 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Gear 5015****ÜRÜN ÖNERİSİ 2****SP Gear 1071**

Kontrol her 80000 km/ 48 ay

HİDROLİK FREN/KAVRAMA SİSTEMİ

Yağlayıcı kapasitesi: 0,53 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Drauliquid-LV Super DOT 4****ÜRÜN ÖNERİSİ 2****Drauliquid-S DOT 4**

Kontrol her 500 km, değişim her 60000 km/ 24 ay

HİDROLİK DİREKSİYON**KULLANIM**

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**ATF Dexron II-D**

Kontrol her 20000 km/ 12 ay



ALFA ROMEO (EU) 156 932 156 1.9 JTD 16V (93 KW) (2002-2005)

SOĞUTMA SİSTEMİ

Yağlayıcı kapasitesi: 6,1 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Coolant -38 Organic NF***Kontrol her 500 km, değişim her 60000 km/ 24 ay*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.