

ALFA ROMEO (EU) BRERA 939 BRERA

2.4 JTDM 20V (153 KW) (2008-2010)

**MOTOR 939A9000**

Yağlayıcı kapasitesi: 6,4 litre

KULLANIM

Esnek (maks)

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Emperol 5W-40**

Değişim her 35000 km

DİFERANSİYELİ ŞANZIMAN DÜZ 6/1

Yağlayıcı kapasitesi: 2,8 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Gear 5015**

Kontrol her 35000 km

HİDROLİK FREN/KAVRAMA SİSTEMİ ABS**KULLANIM**

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Drauliquid-LV Super DOT 4****ÜRÜN ÖNERİSİ 2****Drauliquid-S DOT 4**

Değişim her 35000 km/ 24 ay

HİDROLİK DİREKSİYON**KULLANIM**

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Fluid 3013**

Kontrol her 35000 km

ALFA ROMEO (EU) BRERA 939 BRERA 2.4 JTDM 20V (153 KW) (2008-2010)

**SOĞUTMA SİSTEMİ**

Yağlayıcı kapasitesi: 7,35 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Coolant SP 15+****ÜRÜN ÖNERİSİ 2****Coolant SP 12****ÜRÜN ÖNERİSİ 3****Coolant -38 Organic NF***Kontrol her 35000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.