



ALFA ROMEO (EU) GIULIETTA 940

GIULIETTA 1.4 TURBO (85 KW) (2010-

MOTOR 940A6000
Yağlayıcı kapasitesi: 3,1 litre (Servis ikmali)

KULLANIM	İKLİM
Katı, esnek (maks)	Ilımlı

ÜRÜN ÖNERİSİ 1		
Specialsynth MSP 5W-40		

Değişim her 12 ay

KULLANIM	İKLİM
Esnek (maks)	Ilımlı

ÜRÜN ÖNERİSİ 1		
Specialsynth MSP 5W-40		

Değişim her 30000 km/ 24 ay

DİFERANSİYELİ ŞANZİMAN DÜZ 6/1
Yağlayıcı kapasitesi: 1,9 litre

KULLANIM	İKLİM
Normal	Ilımlı

ÜRÜN ÖNERİSİ 1	ÜRÜN ÖNERİSİ 2	
SP Gear 1081	SP Gear 5015	

Kontrol her 30000 km

HİDROLİK FREN/KAVRAMA SİSTEMİ ABS
Yağlayıcı kapasitesi: 0,8 litre

KULLANIM	İKLİM
Normal	Ilımlı

ÜRÜN ÖNERİSİ 1	ÜRÜN ÖNERİSİ 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Değişim her 24 ay





ALFA ROMEO (EU) GIULIETTA 940 GIULIETTA 1.4 TURBO (85 KW) (2010- 2021)

SÖĞÜTMA SİSTEMLERİ

Yağlayıcı kapasitesi: 5,7 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Coolant SP 14+**

Kontrol her 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.