

**ALFA ROMEO (EU) MITO 955 MITO****1.4 16V TURBO BIFUEL (88 KW) (2011-****2020)****MOTOR** 198A4000 / 940B7000 LPG

Yağlayıcı kapasitesi: 3,3 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Specialsynth MSP 5W-40***Değişim her 30000 km/ 24 ay***KULLANIM**

Zor

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Specialsynth MSP 5W-40***Kontrol her 3000 km, değişim her 10000 km/ 12 ay***DİFERANSİYELİ ŞANZİMAN DÜZ 5/1**

Yağlayıcı kapasitesi: 1,6 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**SP Gear 1081****ÜRÜN ÖNERİSİ 2****SP Gear 5015****HİDROLİK FREN/KAVRAMA SİSTEMİ**

Yağlayıcı kapasitesi: 0-0 litre (Min ve maks. arasında)

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Drauliquid-LV Super DOT 4****ÜRÜN ÖNERİSİ 2****Drauliquid-S DOT 4***Değişim her 30000 km/ 24 ay*



ALFA ROMEO (EU) MITO 955 MITO 1.4 16V TURBO BIFUEL (88 KW) (2011- 2020)

SÖĞÜTMA SİSTEMİ

Yağlayıcı kapasitesi: 6 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1**Coolant SP 14+**

Kontrol her 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.