



ALFA ROMEO (EU) SPIDER 916

SPIDER 3.2 V6 24V (2003-2006)

MOTOR 936A000
Yağlayıcı kapasitesi: 5,9 litre

KULLANIM	İKLİM
Normal	Ilımlı

ÜRÜN ÖNERİSİ 1		
Emperol Racing 10W-60		

DİFERANSİYELİ ŞANZİMAN DÜZ 5/1
Yağlayıcı kapasitesi: 2 litre

KULLANIM	İKLİM
Normal	Ilımlı

ÜRÜN ÖNERİSİ 1	ÜRÜN ÖNERİSİ 2	
SP Gear 1071	Syngear 75W-90	

Kontrol her 80000 km

HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC
Yağlayıcı kapasitesi: 0,6 litre

KULLANIM	İKLİM
Normal	Ilımlı

ÜRÜN ÖNERİSİ 1		
SP Fluid 3013		

Kontrol her 20000 km/ 12 ay

HİDROLİK FREN/KAVRAMA SİSTEMİ ABS
Yağlayıcı kapasitesi: 0,45 litre

KULLANIM	İKLİM
Normal	Ilımlı

ÜRÜN ÖNERİSİ 1	ÜRÜN ÖNERİSİ 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontrol her 20000 km, değişim her 60000 km/ 24 ay

ALFA ROMEO (EU) SPIDER 916

SPIDER 3.2 V6 24V (2003-2006)



HİDROLİK DİREKSİYON

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1

ATF Dexron II-D

Kontrol her 20000 km

SOĞUTMA SİSTEMİ

Yağlayıcı kapasitesi: 11,7 litre

KULLANIM

Normal

İKLİM

İlımlı

ÜRÜN ÖNERİSİ 1

Coolant -38 Organic NF

Kontrol her 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.