## ACURA (USA / CAN) CSX CSX 2.0 (CAN) (2006-2011)



ENGINE K20Z2
Capacity: 5,3 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE
CLIMATE
Flexible (on board maintenance system)

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

TRANSAXLE AUTOMATIC 5/1 Capacity: 5,9-6,5 liter (Dry fill), Capacity: 2,4-2,9 liter (Service fill)				
use Normal	сымате Moderate			
PRODUCT RECOMMENDATION 1 SP Matic 4026				

TRANSAXLE MANUAL 5/1 Capacity: 1,7 liter (Dry fill), Capacity: 1,5 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Gear 5015				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3			
Charles your 1 months sharps even 26 months					

Check every 1 months, change every 36 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m	ax.)			
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		
Check every 1 months, change every 36 months				

PRODUCT RECOMMENDATION

## ACURA (USA / CAN) CSX CSX 2.0 (CAN) (2006-2011)



COOLING SYSTEM Capacity: 6,45-6,6 liter (Dry fill), Capacity: 0,4 liter (Reserve tank), Capacity: 4,2-4,3 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.