PRODUCT RECOMMENDATION

ACURA (USA / CAN) RDX TB1/2 RDX 2.3 TURBO SH-AWD (2011-2012)

ENGINE K23A1
Capacity: 5,8 liter (Dry fill), Capacity: 4,7 liter (Service fill)

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 5W-30	**Presteza MSP 5W-30**	

DIFFERENTIAL REAR
Capacity: 2,5-2,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSFERBOX
Capacity: 0,4-0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Gearlube GL-5 80W-90**	

TRANSMISSION AUTOMATIC 5/1
Capacity: 7,8 liter (Dry fill), Capacity: 2,9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Check every 1 months, change every 36 months

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ACURA (USA / CAN) RDX TB1/2 RDX 2.3 TURBO SH-AWD (2011-2012)

COOLING SYSTEM Capacity: 8,4 liter (Dry fill), Capacity: 7 liter (Service fill)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant SP 14+**		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367