ALFA ROMEO (EU) 33 905 33 1.5 4X4 (1986-1992)



ENGINE Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 10W-40	Classic Racing Oil 15W-50	

Change every 10000 km/ 6 months

DIFFERENTIAL REAR (4x4) Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Chaok avan 20000 km abanan avan 100	

Check every 20000 km, change every 40000 km/24 months

TRANSAXLE MANUAL 5/1 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Charle avery 20000 km change avery 40000 km/24 months		

Check every 20000 km, change every 40000 km/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 12 months

GREASE POINTS/NIPPLES PROPELLER SHAFT SLIDING JOINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Check every 20000 km/ 12 months		•

ALFA ROMEO (EU) 33 905 33 1.5 4X4 (1986-1992)



COOLING SYSTEM Capacity: 7,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Character average 40000 km/ 40 magnifies	

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.