ATLAS GMBH WHEELED LOADERS 4WD 46E DEUTZ F3L-1011F (1994-1995)



ENGINE Deutz F3L-1011			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 250 hours/ 3 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 50 hours			
DIFFERENTIAL FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 1500 hours/ 12 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 500 hours			
DIFFERENTIAL REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 1500 hours/ 12 months			

USE

Initial service

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 500 hours

CLIMATE

Moderate

ATLAS GMBH WHEELED LOADERS 4WD 46E DEUTZ F3L-1011F (1994-1995)



HUB REDUCTIONS FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 1500 hours/ 12 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 500 hours			
HUB REDUCTIONS REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90			
Change every 1500 hours/ 12 months		OI MAATE	
Initial service		CLIMATE Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 500 hours			
HYDRAULIC SYSTEM HYDROSTATIC D	RIVE		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1 Perlus H 46			
Change every 12 months			
use Initial service		CLIMATE Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 46			
Change every 1500 hours			

ATLAS GMBH WHEELED LOADERS 4WD 46E DEUTZ F3L-1011F (1994-1995)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 1500 hours/ 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 500 hours	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
ANTI-FRICTION BEARINGS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
PLAIN BEARINGS	
USE	 CLIMATE
Normal	Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2