ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR40 PERKINS 403D-15T



(2012-2016)

ENGINE Perkins 403D-15T Filter capacity: 5,5 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 8 hours, change every 12 months/ 500 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40		
Check every 8 hours, change every 12 mo	nths/ 500 hours		

DIFFERENTIAL FRONT Capacity: 4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Check every 500 hours, change every 12 months/ 1500 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			

DIFFERENTIAL REAR Capacity: 3,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Check every 500 hours, change eve	rv 12 months/ 1500 hours		

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

Change every 500 hours

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR40 PERKINS 403D-15T



(2012-2016)

(======)		
HUB REDUCTIONS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12	months/ 1500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
HUB REDUCTIONS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12	months/ 1500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
TRANSMISSION Capacity: 0,65 liter		
USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12	months/ 1500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR40 PERKINS 403D-15T



(2012-2016)

HYDRAULIC SYSTEM		
Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 8 hours, change every	/ 24 months/ 3000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Change every 1500 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 8 hours, change every	/ 24 months/ 3000 hours	'

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

COOLING SYSTEM Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 8 hours, change every 24 months/ 3000 hours		

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR40 PERKINS 403D-15T



(2012-2016)

BRAKE SYSTEM RESERVOIR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Check every 500 hours, change every 12 months/ 1500 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Change every 500 hours			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.