

ATLET STACKERS/PICKERS TERGO UMS 160 (2011 AND AFTER)



TRANSMISSION

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 3000 hours*

USE

Cold store (stay-in & in-out)

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Change every 3000 hours*

TRANSMISSION ZF

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 3000 hours*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Change every 3000 hours*

ATLET STACKERS/PICKERS TERGO UMS 160 (2011 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 37 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	

Check every 10 hours, change every 3000 hours

USE		CLIMATE
Cold store (stay-in & in-out)		Arctic
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 10 hours, change every 3000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		

Check every 10 hours, change every 3000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.