

# AUSA FORKLIFT TRUCKS C 200 H COMPACT (4X2) ISUZU 4LE2 (2006 AND AFTER)



**ENGINE** Isuzu 4LE2  
Capacity: 8,18 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SHPD 20W-50</b> |

*Change every 12 months/ 150 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
|-----------------------------|-----------------------------|-----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Change every 12 months/ 150 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SHPD 20W-50</b> |

*Change every 50 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
|-----------------------------|-----------------------------|-----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Change every 50 hours*

**DIFFERENTIAL FRONT**  
Capacity: 4,09 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Check every 40 hours, change every 12 months/ 600 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Change every 50 hours*

# AUSA FORKLIFT TRUCKS C 200 H COMPACT (4X2) ISUZU 4LE2 (2006 AND AFTER)

**HUB REDUCTIONS FRONT**

Capacity: 0,41 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 40 hours, change every 12 months/ 600 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50 hours***TRANSFERBOX**

Capacity: 1,36 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 40 hours, change every 12 months/ 600 hours***HYDRAULIC SYSTEM**

Capacity: 45 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus AF 46***Check every 40 hours, change every 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus AF 46***Change every 50 hours*

# AUSA FORKLIFT TRUCKS C 200 H COMPACT (4X2) ISUZU 4LE2 (2006 AND AFTER)



## HYDRAULIC SYSTEM BRAKING & INCHING

Capacity: 0,9 liter

| USE                         |                                  | CLIMATE                     |
|-----------------------------|----------------------------------|-----------------------------|
| Normal                      |                                  | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> |

Check every 40 hours, change every 12 months/ 900 hours

## GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

## COOLING SYSTEM

Capacity: 6,82 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 40 hours, change every 24 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*