

# MASSEY FERGUSON 4200 MF 4215 (1997-2001)



**ENGINE** Perkins 903.27  
Capacity: 5,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
|-----------------------------------|-----------------------------|-----------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Kroontrak CVT 10W-40</b> |

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL FRONT** AG 105  
Capacity: 7,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 250 hours, change every 1000 hours*

**DIFFERENTIAL FRONT** AG 66/75/85  
Capacity: 5,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 250 hours, change every 1000 hours*

**HUB REDUCTIONS FRONT** AG 105  
Capacity: 1,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 250 hours, change every 1000 hours*

**HUB REDUCTIONS FRONT** AG 62  
Capacity: 0,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 250 hours, change every 1000 hours*

# MASSEY FERGUSON 4200 MF 4215 (1997-2001)



## HUB REDUCTIONS FRONT AG 75/85

Capacity: 1 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 250 hours, change every 1000 hours

## REDUCTION UNITS REAR

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 250 hours, change every 1000 hours

## TRANSAXLE/HYDRAULIC SYSTEM 12/12

Capacity: 50 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak CVT 10W-40</b> |  |          |

Check every 100 hours, change every 1000 hours

## HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

Check every 250 hours, change every 2000 hours

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 250 hours/ 6 months

# MASSEY FERGUSON 4200 MF 4215 (1997-2001)



## COOLING SYSTEM

Capacity: 10 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

### PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 10 hours, change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*