

# MASSEY FERGUSON 6400 DYNA 6470

## DYNA-6/DYNASHIFT TIER II (2006-2007)



**ENGINE** Sisu 44CTA  
Capacity: 14,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3             |
|-----------------------------------|-----------------------------|--------------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Armado Synth LSP Ultra 10W-40</b> |

*Check every 10 hours, change every 400 hours*

**DIFFERENTIAL FRONT** Carraro  
Capacity: 6,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 400 hours, change every 800 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Change every 50 hours*

**DIFFERENTIAL FRONT** Dana  
Capacity: 6,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 400 hours, change every 800 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Change every 50 hours*

# MASSEY FERGUSON 6400 DYNA 6470

## DYNA-6/DYNASHIFT TIER II (2006-2007)



### HUB REDUCTIONS FRONT Carraro

Capacity: 1,1 liter

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Normal                       |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

Check every 400 hours, change every 800 hours

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Initial service              |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

Change every 50 hours

### HUB REDUCTIONS FRONT Dana

Capacity: 1,1 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Check every 400 hours, change every 800 hours

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Initial service             |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

Change every 50 hours

### POWER TAKE OFF FRONT

Capacity: 2,4 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

# MASSEY FERGUSON 6400 DYNA 6470

## DYNA-6/DYNASHIFT TIER II (2006-2007)



### TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 69-71 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak CVT 10W-40</b> |  |          |

Check every 10 hours, change every 1200 hours/ 12 months

### GREASE POINTS/NIPPLES

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Tropical |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Multi Purpose Grease 3</b> |  |          |

Change every 50 hours

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Mediterranean                |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 50 hours

| USE                      |  | CLIMATE |
|--------------------------|--|---------|
| Normal                   |  | Cold    |
| PRODUCT RECOMMENDATION 1 |  |         |
| <b>Gear Grease EP 1</b>  |  |         |

Change every 50 hours

### COOLING SYSTEM

Capacity: 25,5 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

Check every 50 hours, change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.