

**MASSEY FERGUSON 7200 7272 (2000-2002)**

**ENGINE** 645 DSBIEL  
Capacity: 24 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2     |
|--------------------------|------------------------------|
| <b>Multifleet SCD 30</b> | <b>Multifleet SCD 20W-20</b> |

*Check every 10 hours, change every 200 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      |  |
|-------------------------------|--|
| <b>Multifleet SHPD 15W-40</b> |  |

*Check every 10 hours, change every 200 hours/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1  |  |
|---------------------------|--|
| <b>Multifleet SCD 10W</b> |  |

*Check every 10 hours, change every 200 hours/ 12 months*

**FINAL REDUCTION FINAL DRIVE(S)**  
Capacity: 7,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

*Check every 100 hours, change every 500 hours/ 24 months*

**GEARBOX**  
Capacity: 0,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Labora Grease</b>     |  |

*Check every 100 hours*

**MASSEY FERGUSON 7200 7272 (2000-2002)****KNIFE DRIVE GEARBOX**

Capacity: 0,85 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 100 hours, change every 500 hours***TRANSMISSION HYDROSTATIC 3/3**

Capacity: 10,5 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 100 hours, change every 500 hours/ 24 months***HYDRAULIC SYSTEM**

Capacity: 90 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Tropical |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus AF 100</b>     |  |          |

*Check every 10 hours, change every 1000 hours/ 24 months*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 68</b>       | <b>Perlus AF 68</b>      |          |

*Check every 10 hours, change every 1000 hours/ 24 months***GREASE POINTS/NIPPLES**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 50 hours*

**MASSEY FERGUSON 7200 7272 (2000-2002)****COOLING SYSTEM**

Capacity: 50 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 10 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*