

# MASSEY FERGUSON 7400 7485 DYNAV TIER III (2007-2012)



**ENGINE** Sisu 66CTA  
Capacity: 21 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3             |
|-----------------------------------|-----------------------------|--------------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Armado Synth LSP Ultra 10W-40</b> |

*Check every 10 hours, change every 400 hours*

## DIFFERENTIAL FRONT

Capacity: 9 liter, Capacity: 8,5 liter (Suspended front axle)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 400 hours, change every 800 hours*

## HUB REDUCTIONS FRONT HD

Capacity: 0,8 liter, Capacity: 0,6 liter (Suspended front axle)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 400 hours, change every 800 hours*

## HUB REDUCTIONS REAR

Capacity: 13 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 400 hours, change every 1200 hours*

## TRANSAXLE

Capacity: 47-58 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    |  |  |
|-----------------------------|--|--|
| <b>Kroontrak CVT 10W-40</b> |  |  |

*Check every 10 hours, change every 2000 hours*

# MASSEY FERGUSON 7400 7485 DYNAV T TIER III (2007-2012)



## HYDRAULIC SYSTEM

Capacity: 100 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40***Check every 400 hours, change every 1200 hours*

## CLUTCH HOUSING

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013***Check every 400 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multi Purpose Grease 3***Check every 50 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Check every 50 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Gear Grease EP 1***Check every 50 hours*

# MASSEY FERGUSON 7400 7485 DYNAV TIER III (2007-2012)

**COOLING SYSTEM**

Capacity: 28,5 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 400 hours, change every 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*