

MASSEY FERGUSON 8600 MF 8660 (TIER 4I) (2012-2014)



ENGINE Sisu 84AWI
Capacity: 21 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel MSP 15W-40
--	--	---

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT
Capacity: 15 liter (770/504), Capacity: 14 liter (770/510)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 400 hours, change every 800 hours

DIFFERENTIAL FRONT SUSPENDED FRONT AXLE
Capacity: 14,5 liter (770/618), Capacity: 14 liter (770/624)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 400 hours, change every 800 hours

HUB REDUCTIONS FRONT
Capacity: 6 liter (770/510), Capacity: 7 liter (770/618)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 400 hours, change every 800 hours

HUB REDUCTIONS REAR
Capacity: 14 liter (each hub)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
---	--	--

Check every 400 hours, change every 2000 hours

PRODUCT RECOMMENDATION

MASSEY FERGUSON 8600 MF 8660 (TIER 4I)
(2012-2014)



TRANSAXLE Dyna-VT
 Capacity: 85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		

Check every 400 hours, change every 2000 hours

HYDRAULIC SYSTEM
 Capacity: 110 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		

Check every 10 hours, change every 1200 hours

HYDRAULIC CLUTCH SYSTEM
 Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 10 hours, change every 2000 hours

MASSEY FERGUSON 8600 MF 8660 (TIER 4I) (2012-2014)



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multi Purpose Grease 3		

Change every 50 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gear Grease EP 1		

Change every 50 hours

COOLING SYSTEM

Capacity: 34,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 1200 hours

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 60 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.