

# MASSEY FERGUSON 8600 MF 8690 (TIER 4I) (2012-2014)



**ENGINE** Sisu 84AWI  
Capacity: 21 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------------|-----------------------------|------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Check every 10 hours, change every 400 hours*

**DIFFERENTIAL FRONT**  
Capacity: 15 liter (770/504), Capacity: 14 liter (770/510)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 400 hours, change every 800 hours*

**DIFFERENTIAL FRONT SUSPENDED FRONT AXLE**  
Capacity: 14,5 liter (770/618), Capacity: 14 liter (770/624)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 400 hours, change every 800 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 6 liter (770/510), Capacity: 7 liter (770/618)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 400 hours, change every 800 hours*

**HUB REDUCTIONS REAR**  
Capacity: 14 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 400 hours, change every 2000 hours*

# MASSEY FERGUSON 8600 MF 8690 (TIER 4I) (2012-2014)



**TRANSAXLE** Dyna-VT  
Capacity: 85 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 400 hours, change every 2000 hours*

**HYDRAULIC SYSTEM**

Capacity: 110 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 10 hours, change every 1200 hours*

**HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

*Check every 10 hours, change every 2000 hours*

# MASSEY FERGUSON 8600 MF 8690 (TIER 4I) (2012-2014)



## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multi Purpose Grease 3***Change every 50 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 50 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Gear Grease EP 1***Change every 50 hours*

## COOLING SYSTEM

Capacity: 34,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Check every 10 hours, change every 1200 hours*

## SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 60 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*