PRODUCT RECOMMENDATION

MASSEY FERGUSON MF MF 805 (1983-1985)

ENGINE Perkins A6.354.4
Capacity: 15,9 liter, Filter capacity: 1,13 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	**Multifleet SCD 30**	**Multifleet SCD 20W-20**

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SCD 10W**	

Check every 10 hours, change every 250 hours

CYLINDER DRIVE REDUCTION
Capacity: 1,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	**Unigear LS GL-3/GL-5 85W-140**

Check every 100 hours, change every 250 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	**Unigear LS GL-3/GL-5 85W-140**

Check every 100 hours, change every 250 hours/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MASSEY FERGUSON MF MF 805 (1983-1985)

TRANSMISSION MANUAL 3/1
Capacity: 3,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SHPD 15W-40	**Multifleet SCD 30**	**Multifleet SCD 20W-20**

Check every 1 months/ 100 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Kroontrak MTH 10W-30	**Multifleet SCD 10W**	

Check every 1 months/ 100 hours, change every 250 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 27,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Multifleet SHPD 15W-40	**Multifleet SCD 30**	**Multifleet SCD 20W-20**

Check every 50 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Kroontrak MTH 10W-30	**Multifleet SCD 10W**	

Check every 50 hours, change every 500 hours

HYDRAULIC SYSTEM HYDROSTATIC REEL DRIVE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 68	**Perlus AF 68**	

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MASSEY FERGUSON MF MF 805 (1983-1985)

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 21 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Coolant -38 Organic NF	**Coolant -26**

Check every 50 hours, change every 500 hours

WOBBLE BOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	**Unigear LS GL-3/GL-5 85W-140**

Check every 50 hours, change every 250 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367