

MASSEY FERGUSON MF MF 845 (1983-1985)**ENGINE** Perkins AT6.354.4

Capacity: 15,9 liter, Filter capacity: 1,13 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SCD 30	Multifleet SCD 20W-20

Check every 10 hours, change every 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SCD 10W	

*Check every 10 hours, change every 250 hours***CYLINDER DRIVE REDUCTION**

Capacity: 1,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	Unigear LS GL-3/GL-5 85W-140

*Check every 100 hours, change every 250 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 4,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	Unigear LS GL-3/GL-5 85W-140

Check every 100 hours, change every 250 hours/ 12 months

MASSEY FERGUSON MF MF 845 (1983-1985)**TRANSMISSION MANUAL 3/3**

Capacity: 4,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SCD 30	Multifleet SCD 20W-20

Check every 1 months/ 100 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SCD 10W	

*Check every 1 months/ 100 hours, change every 250 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 27,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SCD 30	Multifleet SCD 20W-20

Check every 50 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SCD 10W	

*Check every 50 hours, change every 500 hours***HYDRAULIC SYSTEM HYDROSTATIC DRIVE**

Capacity: 32 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Check every 100 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM HYDROSTATIC REEL DRIVE**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	Perlus AF 68	

MASSEY FERGUSON MF MF 845 (1983-1985)**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Check every 50 hours</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 50 hours, change every 500 hours</i>		

WOBBLE BOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	Unigear LS GL-3/GL-5 85W-140
<i>Check every 50 hours, change every 250 hours/ 12 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.