

**MCCORMICK CX CX 85 (2003-2007)**

**ENGINE AQ../AS..**  
Capacity: 7,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50***Check every 10 hours, change every 250 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 10 hours, change every 250 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 10W-40***Check every 10 hours, change every 250 hours*

**ENGINE RE../RG..**  
Capacity: 7,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50***Check every 10 hours, change every 500 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 10 hours, change every 500 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 10W-40***Check every 10 hours, change every 500 hours*

**MCCORMICK CX CX 85 (2003-2007)****DIFFERENTIAL FRONT MFD**

Capacity: 5 liter

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Normal                       |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

*Check every 250 hours, change every 1000 hours***HUB REDUCTIONS FRONT MFD**

Capacity: 0,6 liter

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Normal                       |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

*Check every 250 hours, change every 1000 hours***POWER TAKE OFF FRONT Hydrac**

Capacity: 0,75 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak MTH 10W-30</b> |  |          |

*Check every 10 hours, change every 250 hours***POWER TAKE OFF FRONT Kitchin**

Capacity: 0,65 liter

| USE                              |                          | CLIMATE                     |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Check every 10 hours, change every 250 hours***TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 34,5-37 liter (Mechanical transmission), Capacity: 49,5 liter (XtraShift 2WD), Capacity: 52 liter (XtraShift MFD)

| USE                              |                          | CLIMATE                     |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Check every 10 hours, change every 1000 hours*

**MCCORMICK CX CX 85 (2003-2007)****GREASE POINTS/NIPPLES**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 50 hours*

**COOLING SYSTEM**

Capacity: 17,5 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 10 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*