

MCCORMICK MTX MTX135 TIER3 (2003-2007)



ENGINE BetaPower 24V
Capacity: 16 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT MFD
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 500 hours

DIFFERENTIAL FRONT INDEPENDENT FRONT SUSPENSION
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 500 hours

MCCORMICK MTX MTX135 TIER3 (2003-2007)



DIFFERENTIAL LIMITED SLIP FRONT INDEPENDENT FRONT SUSPENSION

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 250 hours, change every 500 hours*

HUB REDUCTIONS FRONT WITH BRAKES

Capacity: 2 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 250 hours, change every 500 hours*

HUB REDUCTIONS FRONT WITHOUT BRAKES

Capacity: 1,5 liter (Independent Front Axle), Capacity: 0,6 liter (MFD)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Check every 250 hours, change every 500 hours*

POWER TAKE OFF FRONT

Capacity: 2,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP 220*Check every 10 hours, change every 250 hours*

TRANSMISSION/HYDRAULIC SYSTEM

Capacity: 75 liter, Capacity: 12 liter (extra capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30*Check every 10 hours, change every 1000 hours*

MCCORMICK MTX MTX135 TIER3 (2003-2007)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM

Capacity: 26,5 liter, Capacity: 28,5 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.