ACURA (USA / CAN) INTEGRA INTEGRA 1.8 TYPE R (USA) DC2 (1997-2001)



ENGINE B18C Capacity: 4,8 liter (Dry fill), Capacity: 4 liter	r (Service fill), Filter capacity: 0,3 liter	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Emperol 10W-40		
Change every 12000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 12000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Emperol 10W-40		
Change every 6000 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 6000 km/ 6 months		
TRANSAXLE MANUAL 5/1		
Capacity: 2,1-2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 192000 km/ 72 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 60000 km/ 36 months		

ACURA (USA / CAN) INTEGRA INTEGRA 1.8 TYPE R (USA) DC2 (1997-2001)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change every 36 months		

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Change every 192000 km/ 120 months	
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.