ACURA (USA / CAN) MDX YD3/YD4 MDX 3.5 V6 SH-AWD (USA) (2016-2020)



ENGINE J35Y5 Capacity: 5,4 liter (Service fill), Filter capacity: 0,3 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 12 months		

DIFFERENTIAL REAR

Capacity: 1,82 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSFERBOX Capacity: 0,43 liter		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 30000 miles	,	
USE		CLIMATE
Flexible (on board maintenand	ce system)	Moderate

SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

TRANSMISSION AUTOMATIC 9/1 Capacity: 3,3 liter (Service fill)		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		
Change every 30000 miles		
USE		CLIMATE
Flexible (on board maintenance syste	em)	Moderate

Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		

ACURA (USA / CAN) MDX YD3/YD4 MDX 3.5 V6 SH-AWD (USA) (2016-2020)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
01 00 11		

Change every 36 months

COOLING SYSTEM Capacity: 7,4 liter (Service fill)		
USE		CLIMATE
Flexible (on board maintenance systered	em)	Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.