

ACURA (USA / CAN) TL UA4, UA5 TL 3.2 (CAN) (2001-2001)

**ENGINE J32A1**

Capacity: 4,4 liter, Capacity: 5 liter (Dry fill), Filter capacity: 0,4 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Emperol 10W-40***Change every 6000 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30***Change every 6000 km/ 6 months***TRANSAXLE AUTOMATIC 5/1**

Capacity: 7,2 liter (Dry fill), Capacity: 2,9 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 48000 km/ 24 months***USE**

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 96000 km/ 36 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid DOT 3***Check every 1 months, change every 36 months***POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

ACURA (USA / CAN) TL UA4, UA5 TL 3.2 (CAN) (2001-2001)



COOLING SYSTEM

Capacity: 7,5 liter (Dry fill), Capacity: 5,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 96000 km/ 60 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 192000 km/ 120 months*

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.