

ALFA ROMEO (EU) 159 939 159 2.4 JTDM 20V QTRONIC[□]
(2007-2010)



发动机I939A3000 润滑油容量: 6,4 升 [□]		
使用 灵活 (最大)		气候 温带
产品推荐 1 Emperol 5W-40		


自动驱动桥Iisin Warner AF 40-6 6/1 润滑油容量: 6,1 升 (干式填充), 润滑油容量: 3,3 升 (维修填充) [□]		
使用 正常		气候 温带
产品推荐 1 SP Matic 4026		

液压制动/离合系统, 防抱死制动系统 [□]		
使用 正常		气候 温带
产品推荐 1 Drauliquid-LV Super DOT 4	产品推荐 2 Drauliquid-S DOT 4	

动力转向 [□]		
使用 正常		气候 温带
产品推荐 1 SP Fluid 3013		

润滑点/润滑嘴, 差速器侧 HOMOKINETIC 接头 [□] 润滑油容量: 160 克 [□]		
--	--	--

我们无法为该零件提供标准建议。请与我们的服务部门联系。



ALFA ROMEO (EU) 159 939 159 2.4 JTDM 20V QTRONIC[□] (2007-2010)



润滑点/润滑嘴，车轮侧 HOMOKINETIC 接头[□]

润滑油容量: 282 克[□]

使用		气候
正常		温带
产品推荐 1		
MoS2 Grease EP 2		

冷却系统[□]

润滑油容量: 7,35 升[□]

使用		气候
正常		温带
产品推荐 1	产品推荐 2	产品推荐 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

空调压缩机[□]

润滑油容量: 130 cm³[□]

我们无法为该零件提供标准建议。请与我们的服务部门联系。

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.