

ALFA ROMEO (EU) 164 164 164 3.0 V6(1987-1989)



发动机Ø6412 润滑油容量: 7,5 升 (初始填充), 润滑油容量: 7 升 (维修填充)□		
使用 正常		气候 温带

产品推荐 1 Emperol Racing 10W-60	产品推荐 2 Emperol 10W-40	
---------------------------------	--------------------------	--

使用 正常		气候 北极
----------	--	----------

产品推荐 1 Duranza LSP 5W-30	产品推荐 2 Asyntho 5W-30	
-----------------------------	-------------------------	--

手动驱动桥Ø1 润滑油容量: 1,8 升□		
使用 正常		气候 温带

产品推荐 1 SP Gear 5015	产品推荐 2 Gearlube GL-4 80W	
------------------------	-----------------------------	--

自动驱动桥Ø43 4/1 润滑油容量: 4,2 升□		
使用 正常		气候 温带

产品推荐 1 ATF Dexron II-D		
---------------------------	--	--

自动驱动桥Ø60 4/1 润滑油容量: 4,8 升□		
使用 正常		气候 温带

产品推荐 1 ATF Dexron II-D		
---------------------------	--	--





液压制动/离合系统¹

使用

气候

正常

温带

产品推荐 1

Drauliquid-LV Super DOT 4

产品推荐 2

Drauliquid-S DOT 4

动力转向¹

润滑油容量: 0,9 升¹

使用

气候

正常

温带

产品推荐 1

ATF Dexron II-D

冷却系统¹

润滑油容量: 13 升 (初始填充), 润滑油容量: 9,5 升 (维修填充)¹

使用

气候

正常

温带

产品推荐 1

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.