

ALFA ROMEO (EU) SPIDER 939 SPIDER 2.4 JTDM 20V (147 KW)¹(2006-2008)



发动机I939A3000

润滑油容量: 6,4 升¹

使用		气候
灵活 (最大)		温带
产品推荐 1		
Emperol 5W-40		

手动驱动桥I6/1

润滑油容量: 2,8 升¹

使用		气候
正常		温带
产品推荐 1	产品推荐 2	
SP Gear 5015	Syngear 75W-90	

自动驱动桥Iisin Warner AF 40-6 6/1

润滑油容量: 6,1 升 (干式填充), 润滑油容量: 3,3 升 (维修填充)¹

使用		气候
正常		温带
产品推荐 1		
SP Matic 4026		

液压系统 (顶端) , 电动/液压¹

使用		气候
正常		温带
产品推荐 1		
SP Fluid 3013		

液压制动/离合系统, 防抱死制动系统¹

使用		气候
正常		温带
产品推荐 1	产品推荐 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

ALFA ROMEO (EU) SPIDER 939 SPIDER 2.4 JTDM 20V
(147 KW)[¶](2006-2008)

动力转向□

使用

气候

正常

温带

产品推荐 1

ATF Dexron II-D

冷却系统□

润滑油容量: 7,35 升□

使用

气候

正常

温带

产品推荐 1

Coolant SP 15+

产品推荐 2

Coolant SP 12

产品推荐 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.