

ASTON MARTIN DB7 DB AR1 (2003-2004)**ENGINE**

Capacity: 11 liter, Filter capacity: 1 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Bi-Turbo 15W-40 | Bi-Turbo 20W-50 | |

Change every 12000 km/ 6 months

| USE | | CLIMATE |
|--------------------------|--------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol 5W-40 | Emperol 5W-50 | Emperol Racing 10W-60 |

*Change every 12000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,6 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

*Check every 12000 km/ 6 months, change every 24000 km/ 12 months***TRANSMISSION AUTOMATIC ZF 5HP30 5/1**

Capacity: 12,8 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |

*Check every 12000 km/ 6 months***TRANSMISSION MANUAL Tremec T-56 6/1**

Capacity: 4 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |

Check every 12000 km/ 6 months

ASTON MARTIN DB7 DB AR1 (2003-2004)**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,3 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Check every 12000 km/ 6 months, change every 48000 km/ 24 months

POWER STEERING

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |

Check every 12000 km/ 6 months

COOLING SYSTEM

Capacity: 14,35 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 12000 km/ 6 months, change every 48000 km

AIRCONDITIONING SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.