

PRODUCT RECOMMENDATION

# AUDI (EU) A1, S1 8X A1 2.0 TDI (105 KW) (2011-2015)



## ENGINE CFHD

Capacity: 4-4,3 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Helar SP LL-03 0W-30</b>	<b>Helar SP LL-03 5W-30</b>

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Helar SP LL-03 0W-30</b>	<b>Helar SP LL-03 5W-30</b>

Change every 15000 km/ 12 months

## TRANSAXLE MANUAL 0A8 6/1

Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>

## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Drauliquid-LV Super DOT 4</b>	

Change every 30000 km/ 24 months

## POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Fluid 3013</b>	

Check every 150000 km/ 12 months

PRODUCT RECOMMENDATION

# AUDI (EU) A1, S1 8X A1 2.0 TDI (105 KW) (2011-2015)



## COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Coolant SP 12 EVO**

*Check every 24 months/ 30000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*