

# AMMANN RUBBER TYRED ROLLERS AP AP 240 H CUMMINS 4BT4.5-C99 T3 (2006- 2012)



**ENGINE** Cummins BT4.5-C99  
Capacity: 7 liter

| USE                          |                               | CLIMATE                     |
|------------------------------|-------------------------------|-----------------------------|
| Normal                       |                               | Moderate                    |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Synfleet SHPD 10W-40</b> |

*Check every 20 hours, change every 3 months/ 250 hours*

**WHEEL GEARS**  
Capacity: 2,5 liter (each side)

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Normal                       |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

*Check every 20 hours, change every 12 months/ 1500 hours*

**HYDRAULIC CIRCUIT TRAVEL AND STEERING**  
Capacity: 75 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Perlus H 46</b>       | <b>Perlus H 68</b>       |               |

*Check every 20 hours, change every 24 months/ 2000 hours*

| USE                      |  | CLIMATE |
|--------------------------|--|---------|
| Normal                   |  | Arctic  |
| PRODUCT RECOMMENDATION 1 |  |         |
| <b>Perlus H 32</b>       |  |         |

*Check every 20 hours, change every 24 months/ 2000 hours*

## GREASE POINTS/NIPPLES

| USE                            |                          | CLIMATE                         |
|--------------------------------|--------------------------|---------------------------------|
| Normal                         |                          | Moderate                        |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3        |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> |

*Change every 250 hours/ 3 months*

# AMMANN RUBBER TYRED ROLLERS AP AP 240 H CUMMINS 4BT4.5-C99 T3 (2006-2012)

**COOLING SYSTEM**

Capacity: 20,5 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 20 hours, change every 24 months/ 2000 hours*

**HYDRAULIC CILINDERS FRONT AXLE**

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Perlus H 46</b>       | <b>Perlus H 68</b>       |               |

*Check every 20 hours, change every 24 months/ 2000 hours*

| USE                      |  | CLIMATE |
|--------------------------|--|---------|
| Normal                   |  | Arctic  |
| PRODUCT RECOMMENDATION 1 |  |         |
| <b>Perlus H 32</b>       |  |         |

*Check every 20 hours, change every 24 months/ 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*