

AMMANN SINGLE DIRECTION PLATES AVP 1240 H



ENGINE GX120
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Change every 100 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Change every 1 months/ 20 hours

VIBRATOR UNIT
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 250 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.