

ATLAS GMBH RAILROAD EXCAVATORS

1404ZW (FRICTION WHEEL) (2010 AND AFTER)



ENGINE Deutz BF4M-2012
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	
Multifleet SHPD 20W-50	

Change every 250 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 250 hours

USE	CLIMATE
Initial service (alternative)	Mediterranean

PRODUCT RECOMMENDATION 1	
Multifleet SHPD 20W-50	

Change every 50 hours

USE	CLIMATE
Initial service (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 50 hours

ATLAS GMBH RAILROAD EXCAVATORS 1404ZW (FRICTION WHEEL) (2010 AND AFTER)



DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 2000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 2000 hours*

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 2000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 2000 hours*

HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 2000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 2000 hours*

ATLAS GMBH RAILROAD EXCAVATORS 1404ZW (FRICTION WHEEL) (2010 AND AFTER)



HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 2000 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 2000 hours

TRANSMISSION Powershift

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Multifleet SCD 20W-20

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Change every 2000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Multifleet SCD 20W-20

Change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Change every 500 hours

ATLAS GMBH RAILROAD EXCAVATORS

1404ZW (FRICTION WHEEL) (2010 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 200 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Change every 3000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1
Multifleet SCD 10W

Change every 3000 hours

GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
MoS2 Grease EP 2

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Coolant SP 15+

PRODUCT RECOMMENDATION 2
Coolant SP 12

SWING REDUCTION UNIT

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1
Gearlube Racing 75W-140

Change every 2000 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Change every 2000 hours

ATLAS GMBH RAILROAD EXCAVATORS 1404ZW (FRICTION WHEEL) (2010 AND AFTER)

**SWING RING GEAR TEETH**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Compound OGL EP 0/1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.