

# ATLAS GMBH TRACKED EXCAVATORS

## 260LC (2010 AND AFTER)



**ENGINE** Cummins QSB6.7  
Capacity: 20 liter

| USE       | CLIMATE  |
|-----------|----------|
| Preferred | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3      |
|-------------------------------|---------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet CD+ 15W-40</b> |

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3      |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

**TRANSMISSION** Powershift

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2     |  |
|--------------------------|------------------------------|--|
| <b>Multifleet SCD 30</b> | <b>Multifleet SCD 20W-20</b> |  |

*Change every 2000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Change every 2000 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2     |  |
|--------------------------|------------------------------|--|
| <b>Multifleet SCD 30</b> | <b>Multifleet SCD 20W-20</b> |  |

*Change every 500 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Change every 500 hours*

# ATLAS GMBH TRACKED EXCAVATORS

## 260LC (2010 AND AFTER)



### HYDRAULIC SYSTEM

Capacity: 216 liter (Hydraulic tank), Capacity: 290 liter (System)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Change every 3000 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 3000 hours*

### GREASE POINTS/NIPPLES OTHERS

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### COOLING SYSTEM

Capacity: 42 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 15**

PRODUCT RECOMMENDATION 2

**Coolant SP 15+**

PRODUCT RECOMMENDATION 3

**Coolant SP 12**

### SWING REDUCTION UNIT

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Change every 2000 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 2000 hours*

# ATLAS GMBH TRACKED EXCAVATORS

## 260LC (2010 AND AFTER)



### SWING RING GEAR TEETH

| USE                        |  | CLIMATE  |
|----------------------------|--|----------|
| Normal                     |  | Moderate |
| PRODUCT RECOMMENDATION 1   |  |          |
| <b>Compound OGL EP 0/1</b> |  |          |

### TRAVEL REDUCTION UNIT

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Normal                         |  | Tropical |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>Gearlube Racing 75W-140</b> |  |          |

*Change every 2000 hours*

| USE                       |  | CLIMATE       |
|---------------------------|--|---------------|
| Normal                    |  | Mediterranean |
| PRODUCT RECOMMENDATION 1  |  |               |
| <b>Gearlube LS 80W-90</b> |  |               |

*Change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*