## BARFORD SITE DUMPERS SXR7000 IVECO N45MSSX00 (2007 AND AFTER)



| ENGINE Iveco N45 MSSX00  |               |
|--------------------------|---------------|
| USE                      | CLIMATE       |
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| Agridiesel CRD+ 15W-40   |               |

Change every 300 hours

| USE                        |                          | CLIMATE                       |
|----------------------------|--------------------------|-------------------------------|
| Normal                     |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40     | Armado Synth LSP Ultra 10W-40 |

Change every 300 hours

| DIFFERENTIAL FRONT       |                             |          |
|--------------------------|-----------------------------|----------|
| USE                      |                             | CLIMATE  |
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 600 hours   |                             | •        |

| DIFFERENTIAL REAR        |                             |          |
|--------------------------|-----------------------------|----------|
| USE                      |                             | CLIMATE  |
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 600 hours   |                             | '        |

| TRANSFERBOX O&S                    |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| ATF-F (Ford)                       |          |
| Change every 1200 hours/ 12 months | ·        |

## BARFORD SITE DUMPERS SXR7000 IVECO N45MSSX00 (2007 AND AFTER)



| TRANSMISSION PowerShuttle/ITL      |  |          |
|------------------------------------|--|----------|
| USE                                |  | CLIMATE  |
| Normal                             |  | Moderate |
| PRODUCT RECOMMENDATION 1           |  |          |
| ATF-F (Ford)                       |  |          |
| Change every 1200 hours/ 12 months |  |          |

| HYDRAULIC SYSTEM         |                          |          |
|--------------------------|--------------------------|----------|
| USE                      |                          | CLIMATE  |
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Perlus H 32              | Perlus AF 32             |          |

Change every 1200 hours/ 12 months

| HYDRAULIC BRAKE SYSTEM   |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Perlus H 15              |          |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| COOLING SYSTEM           |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Coolant -38 Organic NF   |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.