BELL EQUIPMENT RIGID TRACTORS & HAULERS 1866A MKIII JOHN DEERE 6068TF250



	RODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
use Normal		climate Moderate
ENGINE John Deere 6068 TF250 Capacity: 19 liter		

Change every 250 hours/ 6 months

DIFFERENTIAL REAR Capacity: 32 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 250 hours, change every 1000 hours

TRANSMISSION Allison 3000 TC415 6/1 Capacity: 26,5 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check even 250 hours, chapter aven 1000 hours		

Check every 250 hours, change every 1000 hours

HYDRAULIC SYSTEM Capacity: 147 liter (Hydraulic system including tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 68	Perlus AF 68		

Check every 250 hours, change every 3000 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS + DRIVE TRAIN			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

BELL EQUIPMENT RIGID TRACTORS & HAULERS 1866A MKIII JOHN DEERE 6068TF250



 COOLING SYSTEM Capacity: 20 liter

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Coolant SP 15+
 Coolant SP 12
 Coolant -38 Organic NF

Change every 24 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.