

BELL EQUIPMENT WHEELED LOADERS L L2208C MERCEDES-BENZ OM442N



ENGINE Mercedes-Benz OM442N
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Change every 100 hours

DIFFERENTIAL FRONT Bell
Capacity: 88 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 100 hours

BELL EQUIPMENT WHEELED LOADERS L L2208C MERCEDES-BENZ OM442N



DIFFERENTIAL REAR Bell
Capacity: 88 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Change every 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1
Unigear LS GL-3/GL-5 85W-140

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Change every 100 hours

BELL EQUIPMENT WHEELED LOADERS L L2208C MERCEDES-BENZ OM442N

**FINAL DRIVES**

Capacity: 10 liter (each)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 1000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 100 hours*

BELL EQUIPMENT WHEELED LOADERS L L2208C MERCEDES-BENZ OM442N



TRANSMISSION Clark 36000 4
Capacity: 37 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gear Oil Alcat 10W	SP Matic 2032	ATF Dexron II-D

Change every 1000 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gear Oil Alcat 10W	SP Matic 2032	ATF Dexron II-D

Change every 100 hours

HYDRAULIC SYSTEM

Capacity: 220 liter (Hydraulic system including tank), Capacity: 180 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Multifleet SCD 10W	

Change every 2000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

BELL EQUIPMENT WHEELED LOADERS L L2208C MERCEDES-BENZ OM442N



COOLING SYSTEM

Capacity: 44 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.