

BELL EQUIPMENT WHEELED LOADERS L L2306C PLUS II JOHN DEERE 6081HF (TIER I)



ENGINE John Deere 6081 HF
Capacity: 25 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Change every 250 hours/ 6 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT ZF MT-L3105
Capacity: 51 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1000 hours

DIFFERENTIAL REAR ZF MT-L3095
Capacity: 43 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1000 hours

BELL EQUIPMENT WHEELED LOADERS L L2306C PLUS II JOHN DEERE 6081HF (TIER I)



TRANSMISSION ZF 4WG260 4/3
Capacity: 38 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	SP Matic 2032

Change every 1000 hours

HYDRAULIC SYSTEM

Capacity: 220 liter (Hydraulic system including tank), Capacity: 180 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Multifleet SCD 10W	

Change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.