## BOBCAT SKID STEER LOADERS 753G S/N 516220000 -> (1999-2003)



ENGINE Kubota V2203-M Capacity: 7,1 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	
Check every 10 hours, change every 250 l	nours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Check every 10 hours, change every 250 h	nours	1
use Normal		сциате Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every 250 h	nours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Check every 10 hours, change every 250 h	nours	
HYDRAULIC SYSTEM HYDROSTATIC D Capacity: 13,2 liter (Hydraulic tank), Capac		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 50 hours, change every 1000	hours/ 12 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Check every 50 hours, change every 1000	hours/ 12 months	

## BOBCAT SKID STEER LOADERS 753G S/N 516220000 -> (1999-2003)



<b>GREASE POINTS/NIPPLES</b>		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 12,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -33 MPG	
Check every 10 hours	

 

 TRAVEL REDUCTION UNIT Capacity: 30 liter (Hydraulic tank)

 CLIMATE Normal

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 Multifleet SHPD 10W-40
 Multifleet SHPD 10W-40

Check every 50 hours, change every 1000 hours/ 12 months

use Normal		climate Arctic	
PRODUCT RECOMMENDATION 1 Asyntho 5W-30			
Check every 50 hours, change every 1000 hours/ 12 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.