

# BOBCAT SKID STEER LOADERS S160

## KUBOTA V2003-T-E2B (2003-2013)



**ENGINE** Kubota V2003-T-E2B  
Capacity: 8,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |
|-------------------------------|--------------------------|
| <b>Multifleet SHPD 20W-50</b> | <b>Multifleet SCD 40</b> |

*Check every 10 hours, change every 250 hours/ 12 months*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Multifleet SCD 30</b> |  |

*Check every 10 hours, change every 250 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 250 hours/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1  |  |
|---------------------------|--|
| <b>Multifleet SCD 10W</b> |  |

*Check every 10 hours, change every 250 hours/ 12 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Tropical |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |
|-------------------------------|--------------------------|
| <b>Multifleet SHPD 20W-50</b> | <b>Multifleet SCD 40</b> |

*Check every 10 hours, change every 50 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>Multifleet SCD 30</b> |  |

*Check every 10 hours, change every 50 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 50 hours*

# BOBCAT SKID STEER LOADERS S160

## KUBOTA V2003-T-E2B (2003-2013)



| USE                                                |  | CLIMATE |
|----------------------------------------------------|--|---------|
| Initial service                                    |  | Cold    |
| PRODUCT RECOMMENDATION 1                           |  |         |
| <b>Multifleet SCD 10W</b>                          |  |         |
| <i>Check every 10 hours, change every 50 hours</i> |  |         |

| FINAL DRIVES                                                    |  |               |
|-----------------------------------------------------------------|--|---------------|
| Capacity: 30,3 liter                                            |  |               |
| USE                                                             |  | CLIMATE       |
| Normal                                                          |  | Mediterranean |
| PRODUCT RECOMMENDATION 1                                        |  |               |
| <b>Perlus AF 100</b>                                            |  |               |
| <i>Check every 50 hours, change every 1000 hours/ 12 months</i> |  |               |

| USE                                                             |                          | CLIMATE                  |
|-----------------------------------------------------------------|--------------------------|--------------------------|
| Normal                                                          |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                                        | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus H 46</b>                                              | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |
| <i>Check every 50 hours, change every 1000 hours/ 12 months</i> |                          |                          |

| USE                                                             |                          | CLIMATE  |
|-----------------------------------------------------------------|--------------------------|----------|
| Acceptable                                                      |                          | Moderate |
| PRODUCT RECOMMENDATION 1                                        | PRODUCT RECOMMENDATION 2 |          |
| <b>Kroontrak MTH 10W-30</b>                                     | <b>HDX 10W</b>           |          |
| <i>Check every 50 hours, change every 1000 hours/ 12 months</i> |                          |          |



# BOBCAT SKID STEER LOADERS S160

## KUBOTA V2003-T-E2B (2003-2013)



### HYDRAULIC SYSTEM HYDROSTATIC DRIVE

Capacity: 18,2 liter (Hydraulic tank), Capacity: 34,1 liter (Total)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus AF 100</b>     |  |  |

*Check every 50 hours, change every 1000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Perlus H 46</b>       | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |

*Check every 50 hours, change every 1000 hours/ 12 months*

| USE        | CLIMATE  |
|------------|----------|
| Acceptable | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2 |  |
|-----------------------------|--------------------------|--|
| <b>Kroontrak MTH 10W-30</b> | <b>HDX 10W</b>           |  |

*Check every 50 hours, change every 1000 hours/ 12 months*

| USE               | CLIMATE  |
|-------------------|----------|
| Biodegradable oil | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

*Check every 50 hours, change every 1000 hours/ 12 months*

### GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 10 hours*

### COOLING SYSTEM

Capacity: 10,2 liter, Capacity: 11,3 liter (with 4 zone airconditioning system)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |  |

*Check every 10 hours, change every 24 months*

# **BOBCAT SKID STEER LOADERS S160 KUBOTA V2003-T-E2B (2003-2013)**



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*