

BOBCAT SKID STEER LOADERS S220

TURBO HF KUBOTA V3300-DI-T (2003-2010)



ENGINE Kubota V3300-DI-T
Capacity: 13,3 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 20W-50	Multifleet SCD 40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 20W-50	Multifleet SCD 40

Check every 10 hours, change every 50 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

Check every 10 hours, change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 50 hours

BOBCAT SKID STEER LOADERS S220

TURBO HF KUBOTA V3300-DI-T (2003-2010)



USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Check every 10 hours, change every 50 hours</i>		

FINAL DRIVES		
Capacity: 41,6 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus AF 100		
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		

USE		CLIMATE
Acceptable		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	HDX 10W	
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		



BOBCAT SKID STEER LOADERS S220

TURBO HF KUBOTA V3300-DI-T (2003-2010)



HYDRAULIC SYSTEM HYDROSTATIC DRIVE

Capacity: 17,8 liter (Hydraulic tank), Capacity: 49,2 liter (Total)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus AF 100		

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Acceptable		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	HDX 10W	

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 10 hours

COOLING SYSTEM

Capacity: 16,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

BOBCAT SKID STEER LOADERS S220 TURBO HF KUBOTA V3300-DI-T (2003-2010)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.