PRODUCT RECOMMENDATION

# CASE MINI EXCAVATORS CK/CX CX20B ZTS YANMAR 3TNV82A (TIER 2) (2005-2012)

## ENGINE Yanmar 3TNV82A
Capacity: 5,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** |

*Check every 10 hours, change every 250 hours/ 3 months*

| USE | CLIMATE |
|---|---|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Synfleet SHPD 10W-40** | **Multifleet SHPD 10W-40** | |

*Check every 10 hours, change every 250 hours/ 3 months*

## HYDRAULIC SYSTEM
Capacity: 20 liter (Hydraulic tank), Capacity: 25 liter (Total)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Perlus H 46** | **Perlus H 32** | **Perlus AF 46** |

*Check every 10 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **MoS2 Grease EP 2** | | |

*Change every 10 hours*

## COOLING SYSTEM
Capacity: 3,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant SP 15+** | **Coolant SP 12** | |

*Check every 10 hours, change every 1000 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CASE MINI EXCAVATORS CK/CX CX20B ZTS YANMAR 3TNV82A (TIER 2) (2005-2012)

## DRIVE CHAIN COMPARTMENTS
Capacity: 0,35 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |
| *Change every 2000 hours* | | |

## SWING RING GEAR TEETH

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **MoS2 Grease EP 2** | | |
| *Change every 50 hours* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367